

Bodro Racing 10W-60

Bodro Racing 10W-60 is a fully synthetic low friction motor oil, formulated to ensure smooth operation in extreme conditions for sporty drivers. The extreme viscosity offers maximum lubrication to enhance performance whilst keeping you safe. The optimal oil pressure keeps your engine well lubricated and minimizes wear during extreme and long-term loads on the engine.



Properties

- + Specially formulated for sports cars
- + Particularly suited for modern injection and turbo engines with high power
- + Excellent fuel economy performance
- + Excellent wear performance technology

Specifications

API SN/CF
 ACEA A3/B4
 BMW Longlife-01
 VW 502 00/505 00
 MB 229.3
 GM LL-B-025
 Porsche A40

Table of properties

Property	Test Method	Unit	Value
Density 15°C	DIN 51757	g/cm ³	0.855
Kinematic Viscosity @ 40°C	ASTM D 7042-04	mm ² /s	168.0
Kinematic Viscosity @ 100°C	ASTM D 7042-04	mm ² /s	24.0
Viscosity Index	ASTM ISO 2909	None	175
Viscosity at -25°C (CCS)	ASTM D 5293	mPas	≤ 7000
Evaporation Loss (Noack)	CEC-L-40-A-93	%	5.3
Pour Point °C	ASTM ISO 3016	°C	-36
Flash Point °C	ASTM ISO 2592	°C	240

* Characteristic values can fluctuate within the normal range. The information in this publication is based on our current knowledge and experience. They do not release the user from their own tests and trials due to possible influences during the processing and application of our products. A legally binding assurance of certain properties or the suitability for a specific application cannot be derived from our information. It is the responsibility of the recipient of our products to observe any property rights as well as existing laws and regulations.

