

Cruiser 10W-30 4T

High-performance motor oil formulated for 4-stroke scooters with a dry clutch and separately lubricated transmission. Provides maximum performance and outstanding engine protection under all operating conditions. Lubrication is provided reliably as well as optimal noise reduction and minimal wear. Special friction reduction properties are given according to the JASO MB specification.



Properties

- + Excellent wear and tear reduction
- + Lowered oil consumption
- + Optimal engine performance
- + Excellent shear stability
- + Optimum lubrication under all operating conditions
- + Anti-friction to reduce abrasions within the engine

Specifications

API SN
JASO MB

Table of properties

Property	Test Method	Unit	Value
Density 15°C	ASTM D 7777	g/cm ³	0.86
Viscosity @ -25°C (CCS)	ASTM D5293	mPas	<=7000
Kinematic Viscosity @ 40°C	ASTM D 7279	cSt	76
Kinematic Viscosity @ 100°C	ASTM D 7279	cSt	11.5
Viscosity Index	ASTM D 2270		145
Pour Point °C	ASTM D 97	°C	-39
Flash Point °C	ASTM D 92	°C	210
NOVAC Evaporation	ASTM D 5800	%	12.9
Colour	ASTM D 1500		3.5

* Characteristic values can fluctuate within the normal range. The information in this publication is based on our current knowledge and experience. They do not release the user from their own tests and trials due to possible influences during the processing and application of our products. A legally binding assurance of certain properties or the suitability for a specific application cannot be derived from our information. It is the responsibility of the recipient of our products to observe any property rights as well as existing laws and regulations.

