

# Galopper 20W-50

Developed for modern car engines with multivalve or turbochargers for both gasoline passenger cars and diesel light duty vehicles. The additives' excellent wear protection properties protect the engine even in the toughest operating conditions.



## Properties

- + Excellent protection to wear and tear
- + Excellent resistance against foaming, corrosion and oxidation
- + High dispersions and detergency level
- + Stable viscosity index

## Specifications

API SL/CF  
 VW 505 00  
 ACEA A3/B2  
 MB 229.1

## Table of properties

Property	Test Method	Unit	Value
Density 15°C	ASTM D 4052	Kg/L	0.86
Kinematic Viscosity @ 40°C	ASTM D 445	cSt	155.5
Kinematic Viscosity @ 100°C	ASTM D 445	cSt	17.7
Viscosity Index	ASTM D 2270		195
Pour Point °C	ASTM D 97		-27.5
Flash Point °C	ASTM D 97		246

\* Characteristic values can fluctuate within the normal range. The information in this publication is based on our current knowledge and experience. They do not release the user from their own tests and trials due to possible influences during the processing and application of our products. A legally binding assurance of certain properties or the suitability for a specific application cannot be derived from our information. It is the responsibility of the recipient of our products to observe any property rights as well as existing laws and regulations.

